



plasma<sup>®</sup>tool

High-efficient **plasma handheld** device for surface treatment. Ergonomically optimized for safe operation in industrial environments.

## Plasmatool – The handheld device with pulsed atmospheric plasma

### Flexible handling and perfect quality at large structures

Surface optimizing prior to gluing or printing is important. The Plasmatool makes chemical primers or mechanical treatments unnecessary. Improved wettability and adhesive force can be achieved at components, which cannot be handled automatically due to size or mobility.

Completely autonomous air supply is integrated inside the device. The operator is independent of any compressed air supply.

The Plasmatool can be used everywhere thanks to the trolley design. Two-handed operation and a signal lamp protect and warn the operators and third parties. The Plasmatool is supplied by a single 230 V power source.

An integrated air compressor supplies the plasma generator. No external gas supplied has to be present.

The handling of the Plasmatool is optimized for easy usage and maximum operator's safety.

- Fine cleaning
- Before coating, laminating and sealing

- Surface functionalisation
- Removal of oxide layers

- Germ reduction
- Activation prior to bonding, sealing, casting or printing

# plasma<sup>®</sup>tool



The perfect tool for **flexible** and **easy** surface treatment in industrial environments.



PB3



PS2000



Handheld

## Technical Information

Electric connection	220 - 240 V AC, 50 - 60 Hz
Max. input current	6 A
Weight	approx. 60 kg
Power consumption	1.300 W
Sound pressure level	< 60 dB (A) by 1 meter distance
Measurements	800 mm x 540 mm x 430 mm

## Features

- Different processes / substrates / geometries
- No PLC necessary
- Stand-Alone unit, no compressed air or mass flow control required
- Only power outlet needed
- Single person handling thanks to trolley design
- Two-handed operation and signal lamp for advanced safety
- Robust and easy to use



**Relyon Plasma GmbH**  
Weidener Straße 16  
93057 Regensburg (Germany)

Tel.: +49 941 60098-0  
Fax: +49 941 60098-100  
[www.relyon-plasma.com](http://www.relyon-plasma.com)

relyon <sup>®</sup>plasma